

RIT-HS7

USB 1D/2D Barcode Scanner



- IP67 zertifiziert
- 3m Fallhöhe
- Eingebaute Std.-Range Honeywell HS7 Scan Engine
- USB-A Kabel 2m

RIT-HS7 Data Sheet

1 Performance																																															
1.1	Image Sensor	1280x800(Megapixel)CMOS																																													
1.2	Aiming	White LED (650nm) Yellow LED																																													
1.3	Resolution:	1280*800																																													
1.4	Field of View :	Horizontal : 44° , Vertical : 28.5°																																													
1.5	Scan Angle :	Roll : 360° , Pitch : ±55° , Skew : ±70°																																													
1.6	Symbologies :	Codabar 、 Code 11、 Code 128、 25、 Code 39 、 Code 93 、 EAN/J AN-13 、 EAN/J AN 8 、 IATA 25、Interleave of 25、 Matirx 25、 MSI 、 GS1DataBar 、 UPC-A 、 UPC Coupon GS1Code 32 (PARAF) 、 EAN-UCC Emulation GS1Data Bar Codablock A、 Codablock F 、 PDF417、 MicroPDF417 Aztec 、 DataMatrix、 MaxiCode、 QR 、 Hanxin,, grid matrix , lattice Australian postal, British postal, Canadian postal , Chinese postal, J apanese postal , Korean postal , Dutch postal , Postnet , Planet																																													
1.7	Typical Depth of Field :	<table border="1"> <thead> <tr> <th></th> <th>Symbology</th> <th>Near (mm [in])</th> <th>Far(mm [in])</th> <th>Difference (mm [in])</th> </tr> </thead> <tbody> <tr> <td>5 MIL</td> <td>C39</td> <td>70 [2.8]</td> <td>311[12.2]</td> <td>246 [9.7]</td> </tr> <tr> <td>10MIL</td> <td>C39</td> <td>40 [1.6]</td> <td>536 [21.1]</td> <td>496 [19.5]</td> </tr> <tr> <td>20 MIL</td> <td>C39</td> <td>68 [2.7]</td> <td>868 [34.2]</td> <td>800 [31.5]</td> </tr> <tr> <td>5 MIL</td> <td>C128</td> <td>75 [3.0]</td> <td>272 [10.7]</td> <td>198[7.8]</td> </tr> <tr> <td>10MIL</td> <td>PDF</td> <td>45 [1.8]</td> <td>425 [16.7]</td> <td>380 [15]</td> </tr> <tr> <td>20 MIL</td> <td>QR</td> <td>57 [2.2]</td> <td>513[20.2]</td> <td>456 [18.0]</td> </tr> <tr> <td>10MIL</td> <td>UPCA</td> <td>44 [1.7]</td> <td>573 [22.6]</td> <td>529 [20.8]</td> </tr> <tr> <td>10MIL</td> <td>DATA MATRIX</td> <td>64 [2.5]</td> <td>297 [11.7]</td> <td>233 [9.2]</td> </tr> </tbody> </table>		Symbology	Near (mm [in])	Far(mm [in])	Difference (mm [in])	5 MIL	C39	70 [2.8]	311[12.2]	246 [9.7]	10MIL	C39	40 [1.6]	536 [21.1]	496 [19.5]	20 MIL	C39	68 [2.7]	868 [34.2]	800 [31.5]	5 MIL	C128	75 [3.0]	272 [10.7]	198[7.8]	10MIL	PDF	45 [1.8]	425 [16.7]	380 [15]	20 MIL	QR	57 [2.2]	513[20.2]	456 [18.0]	10MIL	UPCA	44 [1.7]	573 [22.6]	529 [20.8]	10MIL	DATA MATRIX	64 [2.5]	297 [11.7]	233 [9.2]
	Symbology	Near (mm [in])	Far(mm [in])	Difference (mm [in])																																											
5 MIL	C39	70 [2.8]	311[12.2]	246 [9.7]																																											
10MIL	C39	40 [1.6]	536 [21.1]	496 [19.5]																																											
20 MIL	C39	68 [2.7]	868 [34.2]	800 [31.5]																																											
5 MIL	C128	75 [3.0]	272 [10.7]	198[7.8]																																											
10MIL	PDF	45 [1.8]	425 [16.7]	380 [15]																																											
20 MIL	QR	57 [2.2]	513[20.2]	456 [18.0]																																											
10MIL	UPCA	44 [1.7]	573 [22.6]	529 [20.8]																																											
10MIL	DATA MATRIX	64 [2.5]	297 [11.7]	233 [9.2]																																											
1.8	Resolution:	1D:≥3 mil 2D:≥5 mil																																													
1.9	Print Contrast:	≥20%																																													
2 Working Environment																																															
Environmental																																															
2.1.1	Operating Temperature:	-30° Cto 60° C																																													
2.1.2	Storage Temperature:	-40°Cto 70° C																																													
2.1.3	Humidity:	95%RH , 122°F/50°CNon-condensing																																													
Physical																																															
2.2.1	Operating Voltage:	(3.3V~4.2V) ±5%																																													
2.2.2	Max Current:	330mA																																													
2.2.3	Dimension:	Scanner Size: 180*65*95mmCharge Cradle Size : 170mm*100*80mm																																													
2.2.4	Weight:	388g																																													
2.2.5	Color:	Yellow +Grey																																													
2.2.6	Cable Length:	12m																																													



Wireless

2.3.1	Communication Mode:	USB-A
2.3.2	Prompt Mode:	Buzzer, LED indicator, vibration
2.3.3	Scanning Method:	Trigger Mode/AutoSense Mode
2.3.4	Interface:	USB-A,RS-232 (Optional)
3	Sicherheitsbestimmungen	
3.1	Anti-drop :	Withstand drop from 3 meters high
3.2	Certificate :	CE ROHS FCC

